

HP Injection Valve HDEV 5.2 LC

www.bosch-motorsport.com



- ▶ Max. 500 bar
- ▶ Multi hole
- ▶ Flow rate at 100 bar: up to 1,640 g/min (n-heptane)
- ▶ Spray angle 8 to 20°

The HDEV 5.2 LC is a high pressure injector, which is developed to be used as a port or a direct injector. The function of the HDEV 5.2 LC is both to meter out the fuel and to obtain a well-defined mixture of fuel and air. It is an inward opening solenoid injector which is optimized regarding very short opening and closing times which ensures a very stable linearity at short injection times.

The benefit of this injector is a high spray variability concerning spray angle and spray shape. Also the flow rate can be defined in a big range. Bosch offers the spray targeting design according to the individual customer requirements. If your application conditions will not match the listed performance data, please ask for consultancy at Bosch Motorsport. In addition to the specific designed sample, Bosch offers cost effective production HDEV 5.2 LC on request.

Application

Application at 100 bar (typical)	308 to 1,640 g/min
Fuel input	Top-feed injector
Fuel	Gasoline
Operating pressure	Up to 500 bar
Operating temperature range	-31 to 130°C

Storage temperature range	-40 to 70°C
Max. vibration	600 m/s ²

Technical Specifications

Mechanical Data

Weight w/o wire	Max. 221.5 g
Diameter	20.7 mm
Length standard version	185 mm
Length short version	173 mm
Flow rate at 100 bar (n-heptane)	Up to 1,640 g/min
Number of holes	4 to 7 holes (typical)
Spray type	Multi hole
Spray angle overall	110° (typical)
Spray angle single beam	8 to 20°
Static flow tolerance	±5 %
Dynamic flow tolerance	±6 % at $t_i = 1.5$ ms
Leakage	≤2.5 mm ³ /min at 23°C

Electrical Data

Booster supply	65 to 90 V
Booster current	13.2 A
Booster time	500 µs
Power supply	12 V
Pick up current	9.6 A
Pick up time	800 µs
Hold power supply	12 V
Hold current	3.0 A hysteresis 0.8 A
Coil resistance	1,500 mOhm (ambient temp.)

Connectors and Wires

Mating connector Compact	On request
Connector Jetronic (wire)	D 261 205 288-01
Connector motorsport (wire)	On request
Pin 1	Pos
Pin 2	Gnd

Installation Notes

The injector has to be supplied by a Bosch Motorsport Power Stage Unit (e.g. HPI 5 or HPI 1.16).

Listed electrical values may vary according to the application.

The injector can be cleaned (mechanically or chemically), if the tip will not be damaged.


Do not use supersonic cleaning.

Ordering Information


HP Injection Valve HDEV 5.2 LC

Order number **on request**


Dimensions



Spray variations, further variations on request



Standard version



Short version

Represented by:

Europe:

Bosch Engineering GmbH
Motorsport
Robert-Bosch-Allee 1
74232 Abstatt
Germany
Tel.: +49 7062 911 9101
Fax: +49 7062 911 79104
motorsport@bosch.com
www.bosch-motorsport.de

North America:

Bosch Engineering North America
Motorsport
38000 Hills Tech Drive
Farmington Hills, MI 48331-3417
United States of America
Tel.: +1 248 876 2977
Fax: +1 248 876 7373
motorsport@bosch.com
www.bosch-motorsport.com

Latin America:

Robert Bosch Ltda
Motorsport
Av Juscelino Kubitscheck de
Oliveira 11800
Zip code 81460-900
Curitiba - Parana
Brasilia
Tel.: +55 41 3341 2057
Fax: +55 41 3341 2779

Asia-Pacific:

Bosch Engineering Japan K.K.
Motorsport
18F Queen's Tower C, 2-3-5 Minato Mirai
Nishi-ku, Yokohama-shi
Kanagawa 220-6218
Japan
Tel.: +81 45 650 5610
Fax: +81 45 650 5611
www.bosch-motorsport.jp

Australia, New Zealand and South Africa:

Robert Bosch Pty. Ltd
Motorsport
1555 Centre Road
Clayton, Victoria, 3168
Australia
Tel.: +61 (3) 9541 3901
motor.sport@au.bosch.com